



WIFI-Link™ Technologies Inc.

歲海尼可網路科技有限公司

WEB: <http://www.wifi-link.com.tw/> TEL: 06-2523801 FAX: 06-2526033

TECHNICAL SPECIFICATION								
CABLE TYPE		LOW LOSS 200 COAXIAL CABLE						
STRUCTURE								
Conductor	Composition(No./mm)	1/1.12mm						
	Material	Bare Copper Wire						
	Outside Diameter (mm)	1.12±0.03mm						
Insulation	Material	Gas Injected Foamed Polyethylene						
	Thickness (mm)	0.84mm						
	Nom. Diameter(mm)	2.80 ± 0.1mm						
Shield	Material	(1) Bonded Aluminum Foil			(2) Tinned Copper Wire			
	Construction	0.025mm			16x6/0.12mm			
	Coverage				88%			
	Diameter(mm)				0.12±0.008mm			
Jacket	Material	PVC						
	Diameter(mm)	4.95 ± 0.10m						
	Color	Black						
ELECTRICAL CHARACTERISTIC								
Impedance	Ω	50 ± 3						
Insulation Resistance	MΩ / km	1000 ↑						
Capacitance	PF/M	80.4 ± 3						
Attenuation	Frequency(MHz)	30	150	450	900	1500	1800	2500
	dB/100M	5.8	13.1	22.8	32.6	42.4	46.6	55.4
								